

PRODUCT DATASHEET

Visilux Vision Panel 405 x 405mm

The Visilux Privacy Vision Panel combines toughened glass and top quality stainless steel components within a timber frame, delivering a versatile and robust double-sided observation panel that compliments the healing environment. As standard, the Visilux range features 20mm privacy vision bands which are controlled by either the Kingsway Staff Key or an anti-ligature thumb turn.



Picture Panel

Operation and Maintenance

Operation

To allow vision through the panel, turn the control mechanism 90° clockwise to open the vision bands. Turning the control mechanism in the opposite direction will close the vision bands to prevent vision through the panel. If a 'Soft Close' Visilux is specified, the vision bands will automatically return to the closed position when the control mechanism is released.

Maintenance

Periodic checks should be made to ensure the unit is functioning correctly and is not damaged. Visual checks should also be made to the timber bead to ensure it is fully intact and is holding the panel in place. Fixings should be checked to ensure they remain tight and secure.

Cleaning

Visilux units should be cleaned with caution using a damp cloth if necessary. Avoid the use of excess water or aggressive cleaning agents. The timber beads should be wiped with a dry or damp cloth only to ensure they do not become water damaged.

Guarantee

5 Year Guarantee*

*For faulty manufacture and not for damage

NBS Specification

Typical description would read: Visilux V4400 Vision Panel with Key and Thumb Turn Control

Terms and conditions:

To see our full terms and conditions, please visit:
kingswaygroupglobal.com/terms

VARIATIONS AND DESIGN OPTIONS

Visilux Vision Panel 405 x 405mm

Variations

The Visilux vision panel is available in the following formats:

V4400 - Visilux vision panel 405 x 405mm for a 44mm door with key & anti-ligature thumb turn control

V4401 - Visilux vision panel 405 x 405mm for a 44mm door with key control to both sides

V4402 - Visilux vision panel 405 x 405mm for a 44mm door with anti-ligature thumb turn control to both sides

V4403 - Visilux vision panel 405 x 405mm for a 44mm door with key only control

V4404 - Visilux vision panel 405 x 405mm for a 44mm door with anti-ligature thumb turn only

V4500 - Visilux vision panel 405 x 405mm for a 54mm door with key & anti-ligature thumb turn control

V4501 - Visilux vision panel 405 x 405mm for a 54mm door with key control to both sides

V4502 - Visilux vision panel 405 x 405mm for a 54mm door with anti-ligature thumb turn control to both sides

V4503 - Visilux vision panel 405 x 405mm for a 54mm door with key only control

V4504 - Visilux vision panel 405 x 405mm for a 54mm door with anti-ligature thumb turn only

Terms and conditions:

To see our full terms and conditions, please visit:
kingswaygroupglobal.com/terms

Glazing Specification & Fire Rating

Standard units as shown above have 6mm Trident toughened fire rated glass to both outer faces, these are suitable for FD30 doors.



Design Options

Picture panel add 'P' to the end of the code

Soft Close add 'SC' to the end of the code

Security 150 micron film both sides - add 'F' to end of the product code