

Your Partner in Patient Safety

SOLO Single Action

Door System

The ligature-resistant SOLO Door System provides a robust solution for all single-action opening requirements within a behavioral healthcare facility while minimizing patient safety risks. An extensive choice of ligature-resistant hardware, mechanical & electronic locking options, leaf configurations, vision panels and more ensure your project's unique requirements can be met.



Terms and conditions:

To see our full terms and conditions, please visit: kingswaygroupglobal.com/en-us/terms



SOLO

Key Features & Benefits



Available as single, leaf & a half, or double leaf configurations



Available with full-length continuous hinge – no pivots!



Available with concealed transom closer or recessed side closer



Available with a range of core options, including high-strength tri-laminate FORTUS core



Available with custom frame elevations



Available on KwikShip®



Options available with FSC Chain of Custody Certification



Smoke Rating: UL1784



UL10C certified fire-resistant doorset (20-minutes with hose stream)



COMPLETE DOOR SYSTEM DATASHEET

SOLO Technical Specifications



Technical Specs

Leaf Thickness:

1 ³/₄¹¹

Core Structure Options:

- FORTUS Core (FSC approved trilaminate hardwood)
- Particle Core (PC)
- Solid Composite Lumber Core (SCLC)
- Hollow Metal Steel-Stiffened (HM)

Maximum Opening Dimensions:

- Single Leaf: 48" (w) x 84" (h)
- Double Leaf: 96" (w) x 84" (h)

Lockset Options:

 Choice of mechanical or electronic locking options

Frame Types Available:

 Complete Doorset with 14ga Fully-Welded Hollow Metal Frame

Concealed Door Closer Options:

- KG21 Recessed Side Mounted Door "Closer for use with KG201 Hinge
- KG35 Double Action Transom Closer, for use with KG202 Hinge
- KG36 Double Action Transom Closer, for use with KG202 Hinge
- No Closer

Vision Panel Options:

- Duralux Series Privacy Vision Panels (mechanical)
- Duralux Platinum Series Privacy Vision Panels (electronic)
- Pyrolux Series Clear-Glaze Vision Panels
- No Vision Panel

Smoke Rating:

 Smoke rated to UL1784: the Standard for Safety of Air Leakage Tests of Door Assemblies

Fire Rating:

UL10C (20-minutes with hose stream)

Leaf Configuration:

- Single leaf
- Leaf and a ½
- Double leaf

Robustness Testing:

 Tested to the Department of Health Medium Secure Testing guidelines (view guide <u>here</u>)

Product Code:

- SOD01 (single leaf)
- SOD03 (leaf & half)
- SOD05 (double leaf)

Available Face & Finish Options:

- Wood Veneers
- High-Pressure Laminates (HPL)
- Impact-Resistant Laminates (Palladium, Acrovyn)
- Primed (Wood or Hollow Metal)

See Finishes Swatch Book for full options



3-Year Manufacturer Defect Guarantee as per 'Kingsway Group Product Guarantee' document, a copy of which is available upon request.



Your Partner in Patient Safety

The best ideas always start as conversations

1521 E Avis Dr, Madison Heights, MI 48071 United States

1-800-783-7980 sales@kingswaygroupusa.com

kingswaygroupglobal.com