

COMPLETE DOOR SYSTEM DATASHEET

SENTRY Full-Door Edge Ligature Alarm System

The SENTRY Full Door Edge Alarm System is designed to maximise patient safety and assist clinical staff in preventing loss of life in mental healthcare environments. The SENTRY door features pressure sensors to all three exposed edges of the door which will trigger the staff alarm in the event of a ligature being trapped against them. The SENTRY system works whatever position the door is in open or closed – and is hardwired by design to provide the robustness and reliability demanded for an assistive clinical product within a life-critical system.



Full height sensor to door edge



Optional recessed KG75 electro handle for patient to release door from the inside



Terms and conditions:

To see our full terms and conditions, please visit: kingswaygroupglobal.com/en-au/terms



SENTRY

Key Features & Benefits



Full door edge ligature monitors covering all exposed edges for enhanced safety!



Compatible with Kingsway's KOSMOS Smart Monitoring System and all major annunciators



Detects ligatures regardless of the door's position - open or closed!



Full-length continuous hinge – no pivots!



Available with concealed transom closers



High-strength tri-laminate FORTUS core

Doorset Types Available:









The SENTRY Full Door Edge Alarm System is available in SWING, SWITCH, SOLO and STOW doorset specifications and, as such, it is the most versatile ligature alarmed door system available.



COMPLETE DOOR SYSTEM DATASHEET

SWING SENTRY Full-Door Edge Ligature Alarm System

The SWING SENTRY is a ligature-alarmed, anti-barricade door system designed for service user bedrooms or communal spaces to enhance safety. The doorset features pressure sensors to all three exposed edges of the door which will trigger the staff alarm in the event of a ligature being trapped against them. Thanks to the double-action SwingHinge and unique SwingThru Strike Plate, staff can open the SWING SENTRY doorset outwards in seconds to overcome a barricade – even with the lockbolt extended.



Terms and conditions:

To see our full terms and conditions, please visit: kingswaygroupglobal.com/en-au/terms



SWING SENTRY

Key Features & Benefits



Full door edge ligature monitors covering all exposed edges for enhanced safety!



Compatible with Kingsway's KOSMOS Smart Monitoring System and all major annunciators



Detects ligatures regardless of the door's position - open or closed!



Overcome barricades in seconds – even with the lockbolt extended



No need to unlock the door to overcome a barricade



Full-length continuous hinge – no pivots!



Single key controls the antibarricade device & vision panel - no additional tools required!



Available with concealed transom closers



High-strength tri-laminate FORTUS core



SWING SENTRY Technical Specifications

Technical Specs

Leaf Thickness:

54mm

Core Structure:

 FORTUS Core: solid timber core of 3-layer hardwood

Maximum Leaf Dimensions:

• 1200mm (W) x 2100mm (H)

Lockset Options:

• Choice of mechanical or electronic locking options

Available Facings:

 Classic Veneers / Classic Laminate Woods / Classic Laminate Colours / Signature Laminates available on request - see finishes swatch book for full options

Anti-ligature Ironmongery:

Choice of door furniture (view range <u>here</u>)

Concealed Door Closer Options:

- KG35 Double Action Transom Closer
- KG36 Double Action Transom Closer (Mechanical Hold Open)
- KG37 Double Action Transom Closer (Free Swing)
- KG38 Double Action Transom Closer (Electro Hold Open)
- No Closer

Vision Panel Options:

- Duralux / Duralux Platinum (Square or Oblong)
- Visilux / Visilux Platinum (Square or Oblong)
- Pyrolux (Square or Oblong)
- No Vision Panel

Leaf Configuration:

• Single leaf / Leaf and a ½ / Double Leaf

Robustness Testing:

 Tested to the Department of Health Medium Secure Testing guidelines (view guide <u>here</u>)

Door Sensor Product Codes:

- KG510 SENTRY door top sensor
- KG520 SENTRY door bottom sensor
- KG530 SENTRY door edge sensor

Product Code:

- SWD-SEN02 (54mm single leaf)
- SWD-SEN04 (54mm leaf & half)
- SWD-SEN06 (54mm double leaf)





COMPLETE DOOR SYSTEM DATASHEET

SWITCH SENTRY Full-Door Edge Ligature Alarm System

The SWITCH SENTRY door system features pressure sensors to all three exposed edges of the door that will trigger the staff alarm if a ligature is trapped against them. It is the world's only ligature-alarmed doorset with a hinge-side anti-barricade mechanism, enhancing the safety of staff by positioning them in the barricade 'Green Zone'; the point at which the opening door is at its lowest speed. From the Green Zone, staff can open the doorset outwards in seconds even with the lock bolt extended, saving crucial time during an emergency.



Terms and conditions:

To see our full terms and conditions, please visit: kingswaygroupglobal.com/en-au/terms



SWITCH SENTRY

Key Features & Benefits



Full door edge ligature monitors covering all exposed edges for enhanced safety!



Compatible with Kingsway's KOSMOS Smart Monitoring System and all major annunciators



Detects ligatures regardless of the door's position - open or closed!



Keep staff safe in the barricade 'Green Zone' where the opening door moves slowest



Full-length continuous hinge – no pivots!



Single key control for the antibarricade hinge & vision panel – no additional tools required!



Hinge retracts to open outwards in seconds - no need to unlock the door to overcome a barricade!



Rebated timber frame on closing edge for enhanced strength and acoustic performance



Available with concealed transom closers



High-strength tri-laminate FORTUS core



SWITCH SENTRY Technical Specifications

Technical Specs

Leaf Thickness:

• 54mm

Core Structure:

 FORTUS Core: solid timber core of 3-layer hardwood

Maximum Leaf Dimensions:

• 1200mm (W) x 2100mm (H)

Lockset Options:

 Choice of mechanical or electronic locking options

Available Facings:

 Classic Veneers / Classic Laminate Woods / Classic Laminate Colours / Signature Laminates available on request - see finishes swatch book for full options

Anti-ligature Ironmongery:

Choice of door furniture (view range <u>here</u>)

Concealed Door Closer Options:

- KG35 Double Action Transom Closer
- KG36 Double Action Transom Closer (Mechanical Hold Open)
- KG37 Double Action Transom Closer (Free Swing)
- No Closer

Vision Panel Options:

- Duralux / Duralux Platinum (Square or Oblong)
- Visilux / Visilux Platinum (Square or Oblong)
- Pyrolux (Square or Oblong)
- No Vision Panel

Leaf Configuration:

• Single leaf / Leaf and a ½

Robustness Testing:

 Tested to the Department of Health Medium Secure Testing guidelines (view guide <u>here</u>)

Door Sensor Product Codes:

- KG510 SENTRY door top sensor
- KG520 SENTRY door bottom sensor
- KG530 SENTRY door edge sensor

Product Code:

- SCH-SEN02 (54mm single leaf)
- SCH-SEN04 (54mm leaf & half)





COMPLETE DOOR SYSTEM DATASHEET

SOLO SENTRY Full-Door Edge Ligature Alarm System

The SOLO SENTRY is a ligature-alarmed, single action door system designed to enhance safety in mental healthcare environments. The SOLO SENTRY features pressure sensors to all three exposed door edges which will trigger the staff alarm in the event of a ligature being trapped against them. The doorset provides a robust solution for single action requirements within a mental health facility and is available with a wide variety of lockset options, leaf configurations and anti-ligature hardware choices to meet the needs of your facility, staff and service users.



Terms and conditions:

To see our full terms and conditions, please visit: kingswaygroupglobal.com/en-au/terms



SOLO SENTRY

Key Features & Benefits



Full door edge ligature monitors covering all exposed edges for enhanced safety!



Compatible with Kingsway's KOSMOS Smart Monitoring System and all major annunciators



Detects ligatures regardless of the door's position - open or closed!



Available with a full-length continuous hinge – no pivots!



Rebated timber frame on closing edge for enhanced strength



Available with concealed transom closers



High-strength tri-laminate FORTUS core



SOLO SENTRY Technical Specifications

Technical Specs

Leaf Thickness:

• 54mm

Core Structure:

 FORTUS Core: solid timber core of 3-layer hardwood

Maximum Leaf Dimensions:

• 1200mm (W) x 2100mm (H)

Lockset Options:

Choice of mechanical or electronic locking options

Available Facings:

 Classic Veneers / Classic Laminate Woods / Classic Laminate Colours / Signature Laminates available on request - see finishes swatch book for full options

Anti-ligature Ironmongery:

Choice of door furniture (view range <u>here</u>)

Concealed Door Closer Options:

- KG35 Double Action Transom Closer
- KG36 Double Action Transom Closer (Mechanical Hold Open)
- KG37 Double Action Transom Closer (Free Swing)
- KG38 Double Action Transom Closer (Electro Hold Open)
- No Closer

Vision Panel Options:

- Duralux / Duralux Platinum (Square or Oblong)
- Visilux / Visilux Platinum (Square or Oblong)
- Pyrolux (Square or Oblong)
- No Vision Panel

Leaf Configuration:

• Single leaf / Leaf and a ½ / Double leaf

Robustness Testing:

 Tested to the Department of Health Medium Secure Testing guidelines (view guide <u>here</u>)

Door Sensor Product Codes:

- KG510 SENTRY door top sensor
- KG520 SENTRY door bottom sensor
- KG530 SENTRY door edge sensor

Product Code:

- SOD-SEN02 (54mm single leaf)
- SOD-SEN04 (54mm leaf & half)
- SOD-SEN06 (54mm double leaf)





COMPLETE DOOR SYSTEM DATASHEET

STOW SENTRY Full-Door Edge Ligature Alarm System

The STOW SENTRY is a ligature-alarmed door system featuring a secondary recessed frame to provide clinical teams with greater control and flexibility over how the door is used in mental healthcare environments. To enhance patient safety in high-risk areas, the STOW SENTRY features pressure sensors to all three exposed door edges which will trigger the staff alarm in the event of a ligature being trapped against them.



Terms and conditions:

To see our full terms and conditions, please visit: kingswaygroupglobal.com/en-au/terms



STOW SENTRY

Key Features & Benefits



Full door edge ligature monitors covering all exposed edges for enhanced safety!



Compatible with Kingsway's KOSMOS Smart Monitoring System and all major annunciators



Detects ligatures regardless of the door's position - open or closed!



Door can be locked back flush to the wall in the open position



Unique top plate minimises ligature risks



Full-length continuous hinge for enhanced strength – no pivots!



High-strength tri-laminate FORTUS core

Maximising Staff Control

The STOW doorset offers simple operation whilst maximising staff's control over how a space is used based on clinical assessment:

Free Usage:

If deemed safe, staff can unlock the door allowing service users to open and close it at will.

Stowed:

If a moving door is deemed unsafe but access is still required, staff can securely 'stow' the door leaf flush with the wall for safe passage and observation.

Locked:

If clinical assessment deems it necessary, staff can lock the door shut to minimise risk.



STOW SENTRY Technical Specifications

Technical Specs

Leaf Thickness:

• 54mm

Core Structure:

 FORTUS Core: solid timber core of 3-layer hardwood

Maximum Leaf Dimensions:

• 1200mm (W) x 2100mm (H)

Lockback Frame:

- FAW(90) 90° Frame Profile
- FAW(180) 180° Frame Profile

Lockset Options:

• Choice of mechanical locking options

Available Facings:

 Classic Veneers / Classic Laminate Woods / Classic Laminate Colours / Signature Laminates available on request - see finishes swatch book for full options

Anti-ligature Ironmongery:

KG80 Recessed Handle

Robustness Testing:

 Tested to the Department of Health Medium Secure Testing guidelines (view guide <u>here</u>)

Door Sensor Product Codes:

- KG510 SENTRY door top sensor
- KG520 SENTRY door bottom sensor
- KG530 SENTRY door edge sensor

Product Code:

• STW-SEN02 (54mm single door leaf)






SENTRY Finishes

Laminates:





Woods:




Acrovyn Solids:



Acrovyn Faux Wood & Metal:

Taupe Concrete Black Concrete





The best ideas start with a conversation

144/146 Russell St Emu Plains NSW 2750

1800 325 175 sales@kingswaygroupau.com

kingswaygroupglobal.com