

# SOLO Single Action Door System



## Product datasheet

The SOLO door system is for single action doors in mental health environments.



The SOLO single action door system has been created to provide a robust solution for all door openings that have a single direction of opening, with a wide range of vision panel, hardware and locking options the SOLO door system can be specified to the exact requirements of the project

### Technical Specs

**Leaf Thickness:**  
44mm or 54mm

**Available Facings:**  
Classic Veneers, Classic Laminates and Signature Laminate - see Finishes Swatch Book.

**Lippings for Veneer Facings:**  
Hardwood 10mm to all four sides concealed

**Lippings for Laminate Facings:**  
Hardwood 10mm to all four sides exposed

**Maximum Leaf Dimensions:**  
1000mm (W) x 2100mm (H)

**Core Structure:**  
Solid timber core of 3 layer hardwood

**Vision Panel Options:**  
Duralux, Visilux or Pyrolux ranges

#### Door Closer Options

KG21 Recessed side mounted door closer

KG35 standard, KG36 hold-open and KG37 free-swing transom mounted door closers.

**Fire Rating:**  
NFR / FD30S / FD60S

**Product Codes:**  
SOD01 (44mm single leaf)  
SOD02 (54mm single leaf)  
SOD03 (44mm leaf & half)  
SOD04 (54mm leaf & half)  
SOD05 (44mm double leaf)  
SOD06 (54mm double leaf)



Doorset Solutions  
Certified by BMTRADA