

# SWING Anti-Barricade Door System



## Product datasheet

Double action, anti-barricade door system with unique SwingThru strike plate to allow door to open - even when locked.



SwingThru strike plate

Available with transom mounted integrated door closer



The SWING door system uses the SwingStop hinged doorstop and the SwingHinge double action hinge for a fast method of overcoming barricade situations.

### Technical Specs

**Leaf Thickness:**  
44mm or 54mm

**Available Facings:**  
Classic Veneers, Classic Laminates and Signature Laminate - see Finishes Swatch Book.

**Lippings for Veneer Facings:**  
Hardwood 10mm to all four sides concealed

**Lippings for Laminate Facings:**  
Hardwood 10mm to all four sides exposed

**Maximum Leaf Dimensions:**  
1000mm (W) x 2100mm (H)

**Core Structure:**  
Solid timber core of 3 layer hardwood

**Vision Panel Options:**  
Duralux, Visilux or Pyrolux ranges

**Door Closer Options:**  
KG35 standard, KG36 hold-open and KG37 free-swung transom mounted door closers.

**Fire Rating:**  
FD30S

**Product Codes:**  
SWD01 (44mm single leaf)  
SWD02 (54mm single leaf)  
SWD03 (44mm leaf & half)  
SWD04 (54mm leaf & half)  
SWD05 (44mm double leaf)  
SWD06 (54mm double leaf)



Doorset Solutions  
Certified by BMTRADA