

SWITCH Anti-Barricade System



Product datasheet

SWITCH is the revolutionary anti-barricade door system that operates from the hinge side to keep staff safe in the barricade 'green zone'




Where do your staff stand?
Keep them safe, keep them in the
Green Zone

In the event of a barricade the patented SWITCH hinge mechanism unlocks and folds to allow door to swing outwards.


How the SWITCH system works



Staff approach the barricaded door on the hinge side - in the safe barricade 'green zone'.



Staff unlock the SWITCH hinge from the central key lock.



The door can be safely opened outwards in under 3 seconds.

Technical Specs

Leaf Thickness:
44mm or 54mm

Leaf Configuration:
Single leaf and Leaf & 1/2

Available Facings:
Classic Veneers, Classic Laminates and Signature Laminates - see Finishes Swatch Book

Lippings for Veneer Facings:
Hardwood 10mm to all four sides concealed

Lippings for Laminate Facings:
Hardwood 10mm to all four sides exposed

Maximum Leaf Dimensions:
1000mm (W) x 2100mm (H)

Core Structure:
Solid timber core of 3 layer hardwood

Vision Panel Options:
Duralux, Visilux or Pyralux ranges

Door Closer Options:
KG35 standard, KG36 hold-open and KG37 free-swing transom mounted door closers.

Firerating:
NFR / FD30S

Product Code:
SCH01 (44mm single leaf)
SCH02 (54mm single leaf)
SCH03 (44mm leaf & half)
SCH04 (54mm leaf & half)



Doorset Solutions
Certified by BMTRADA